



KaozhengPro

IT認證考試題庫 專業平臺

考證寶提供最新考古題與模擬試題
協助您高效通過認證考試

www.kaozhengpro.com

Exam : **HPE0-G05**

Title : HPE Morpheus Enterprise
Software Automation
Specialist Exam

Version : DEMO

1.What is the primary function of an "Archive" in the HPE Morpheus Enterprise Library?

- A. To securely store a password or API key.
- B. To store a single, executable script (like Bash or Python).
- C. To store a compressed file bundle (e.g., .zip, .tar.gz) that contains multiple files and directories for deployment.
- D. To define a multi-tier application's structure.

Answer: C

2.A Cloud Administrator's "File/Archive" Task fails.

The log shows:

Executing file task...

Fetching archive: library/my-app.tar.gz

Archive fetched successfully.

Extracting archive to: /root/my-app

Error: Failed to extract archive: tar: /root/my-app: Cannot open: Permission denied

Task failed.

What is the most likely cause of this specific "Permission denied" error?

- A. The "Source" path in the Task configuration is incorrect.
- B. The archive `my-app.tar.gz` is password-protected.
- C. The archive file in the Library is corrupted.
- D. The `morpheus-agent` (or SSH user) does not have permission to write to the `/root/` directory.

Answer: D

3.A System Administrator is building a comprehensive Task. This Task needs to securely retrieve a database password from Cypher and then use that password within a Python script to connect to the database.

Which of the following elements are required to build this single Task? (Select all that apply.)

- A. The password must be passed as an Environment Variable to the script.
- B. The script content must import the `morpheus.cypher` library to read the secret at runtime.
- C. The script content must use `<%=cypher.read('secret/db/pass')%>` to interpolate the password.
- D. The "Task Type" must be set to "Python".
- E. The "Execute Target" must be set to "local".

Answer: A, C, D

4.A System Administrator is troubleshooting a Request Script that is failing to correctly modify a URL.

The initial URL from the Option List is: `https://api.example.com/v1/locations`

The Request Script is:

```
var region = params.customOptions.region; // User selected "emea"
request.url + "?region=" + region;
```

The API call fails, and the log shows the request was made to `https://api.example.com/v1/locations` (the original URL), not the filtered one.

What is the error in the Request Script?

- A. The script should be using `request.params` instead of `request.url`.
- B. The script is missing a `return` statement.

- C. The ``params.customOptions.region`` variable is not available in Request Scripts.
- D. The script is only performing string concatenation; it is not re-assigning the new value back to the ``request.url`` property.

Answer: D

5.A DevOps Engineer is troubleshooting a failed App Blueprint deployment. The 'web' tier fails because it cannot connect to the database.

The 'web' tier's configuration file template uses the variable ``<%=db.internalIp%>``.

The execution log for the 'web' tier's configuration task shows:

[10:30:01] Generating config file...

[10:30:02] Rendered config: connect_ip =

[10:30:03] Error: connect_ip is null.

Which of the following issues in the App Blueprint YAML would cause the ``<%=db.internalIp%>`` variable to be null? (Select all that apply.)

- A. The variable syntax is incorrect; it should be ``<%=instance.db.internalIp%>``.
- B. The ``environmentPrefix`` on the 'db' tier's ``linkedTiers`` setting is set to ``database`` instead of ``db``.
- C. The 'db' tier's instance failed to provision and never acquired an IP address.
- D. The 'web' tier is missing a ``linkedTiers`` property that references the 'db' tier.
- E. The 'db' tier's ``bootOrder`` is set to '1' and the 'web' tier's ``bootOrder`` is set to '0'.

Answer: B, C, D, E