



IT認證考試題庫 專業平臺

考證寶提供最新考古題與模擬試題
協助您高效通過認證考試

www.kaozhengpro.com

Exam : HPE0-S58

**Title : Implementing HPE
Composable Infrastructure
Solutions Exam**

Version : DEMO

1. During an initial setup of a Synergy environment, an integrator needs to enable or disable authorized Service access.

What will be the outcome when the integrator disables this service?

- A. Authenticated administrators will be unable to make changes to the system
- B. Authorized users will be unable to generate a support dump
- C. Authenticated administrators will be unable to access the system
- D. Authorized support will be unable to diagnose the system

Answer: D

Explanation:

Reference: https://support.hpe.com/hpsc/doc/public/display?docId=emr_na-c05098314 (62)

2. FILL BLANK

A customer has the following configuration:

Frame 1

- Bay 1 – HPE Synergy 12Gb SAS Connection Module
- Bay 2
- Bay 3 – HPE Virtual Connect SE 40 GB F8 Module
- Bay 4 – HPE Synergy 12GB SAS Connection Module
- Bay 5
- Bay 6 – HPE Synergy 10 Gb Interconnect Link Module

Frame 2

- Bay 1 – HPE Synergy 12Gb SAS Connection Module
- Bay 2
- Bay 3 – HPE Synergy 10Gb Interconnect Link Module
- Bay 4 – HPE Synergy 12Gb SAS Connection Module
- Bay 5
- Bay 6 – HPE Virtual Connect SE 40Gb F8 Module

How many more frames can the customer add to their Synergy composable fabric? (Note: Enter your answer in the answer field below.)

Answer:

Explanation:

Frame 1 – Bay 2 – HPE Virtual Connect SE 100Gb F32 Module for Synergy (867796-B21)

Frame 1 – Bay 5 – HPE Virtual Connect SE 16Gb Fibre Channel Module for Synergy (779227-B21)

Frame 2 – Bay 2 – Brocade 16Gb/24 Power Pack+ Fibre Channel SAN Switch Module for HPE Synergy (K2Q86A)

Frame 2 – Bay 5 – HPE Synergy 4820C 10/20/25Gb Converged Network Adapter (876449-B21)

3. In a 3-frame HPE Synergy environment, how should an integrator place the image Streamer modules to allow for redundancy to all of the management connections?

- A. one Image Streamer module in frame 2, and a second Image Streamer Module in frame 3 (2 total)
- B. two Image Streamer modules in frame 2, and two Image Streamer modules in frame 3 (4 total)
- C. one Image Streamer module in each Synergy frame (3 total)
- D. two Image Streamer modules in frame 1 (2 total)

Answer: B

Explanation:

Reference: https://www.karma-group.ru/upload/iblock/2be/synergy_image_streamer.pdf (page 7)

4.What must an integrator do before an existing cluster can be imported to the HPE Composer?

- A. The vCenter Server must be integrated with the HPE Composer
- B. The cluster must be vSAN enabled
- C. The HPE Composer must have at least two management interfaces to connect to the cluster
- D. The cluster must be enabled for HPE Composer integration

Answer: A

5.Refer to the exhibit.

Interconnect Bay



Rear of HPE Synergy Frame

How should an integrator pair interconnect bays to set up redundant fabrics in an HPE Synergy 12000 Frame?

- A. Interconnect bays 1 and 2; bays 3 and 4; bays 5 and 6.
- B. Interconnect bays 1 and 6; bays 2 and 5; bays 3 and 4.
- C. Interconnect bays 1 and 4; bays 2 and 5; bays 3 and 6.
- D. Interconnect bays 1 and 3; bays 2 and 4; bays 5 and 6.

Answer: C

Explanation:

Reference: <https://h20195.www2.hp.com/v2/GetPDF.aspx/c04815113.pdf>