



IT認證考試題庫 專業平臺

考證寶提供最新考古題與模擬試題
協助您高效通過認證考試

www.kaozhengpro.com

Exam : **NSE7_OTIS-6.4**

Title : Fortinet NSE 7 - OT Security
6.4

Version : DEMO

1.An OT network administrator is trying to implement active authentication.

Which two methods should the administrator use to achieve this? (Choose two.)

- A. Two-factor authentication on FortiAuthenticator
- B. Role-based authentication on FortiNAC
- C. FSSO authentication on FortiGate
- D. Local authentication on FortiGate

Answer: A,B

2.An OT administrator is defining an incident notification policy using FortiSIEM and would like to configure the system with a notification policy. If an incident occurs, the administrator would like to be able to intervene and block an IP address or disable a user in Active Directory from FortiSIEM.

Which step must the administrator take to achieve this task?

- A. Configure a fabric connector with a notification policy on FortiSIEM to connect with FortiGate.
- B. Create a notification policy and define a script/remediation on FortiSIEM.
- C. Define a script/remediation on FortiManager and enable a notification rule on FortiSIEM.
- D. Deploy a mitigation script on Active Directory and create a notification policy on FortiSIEM.

Answer: C

Explanation:

Reference:

https://fortinetweb.s3.amazonaws.com/docs.fortinet.com/v2/attachments/06918379-afd1-11e9-a989-00505692583a/Standalone_PDF.pdf

3.An OT supervisor has configured LDAP and FSSO for the authentication. The goal is that all the users be authenticated against passive authentication first and, if passive authentication is not successful, then users should be challenged with active authentication.

What should the OT supervisor do to achieve this on FortiGate?

- A. Configure a firewall policy with LDAP users and place it on the top of list of firewall policies.
- B. Enable two-factor authentication with FSSO.
- C. Configure a firewall policy with FSSO users and place it on the top of list of firewall policies.
- D. Under config user settings configure set auth-on-demand implicit.

Answer: D

4.Which three Fortinet products can be used for device identification in an OT industrial control system (ICS)? (Choose three.)

- A. FortiNAC
- B. FortiManager
- C. FortiAnalyzer
- D. FortiSIEM
- E. FortiGate

Answer: A,C,D

5.Refer to the exhibit.

```
config system interface
  edit VLAN101_dmz
    set forward-domain 101
next
  edit VLAN101_internal
    set forward-domain 101
end
```

Given the configurations on the FortiGate, which statement is true?

- A. FortiGate is configured with forward-domains to reduce unnecessary traffic.
- B. FortiGate is configured with forward-domains to forward only domain controller traffic.
- C. FortiGate is configured with forward-domains to forward only company domain website traffic.
- D. FortiGate is configured with forward-domains to filter and drop non-domain controller traffic.

Answer: A